

MISTRAL AUTOMATIC WATER SOFTENERS



Mistral

Selection guide

Selection guide



MODEL	HEIGHT	PEOPLE DAYS*	USAGE
MISTRAL 613	535 mm	3	1 to 2 persons
MISTRAL 817	640 mm	9	average household
MISTRAL 919	685 mm	15	medium household - compact
MISTRAL 822	780 mm	15	medium household
MISTRAL 1023	820 mm	24	larger household or small commercial

* Divide by the number in the household for the average time between regeneration at 280 ppm hardness.

Litres of softened water between regenerations

MODEL	At 200 ppm	At 300 ppm	At 350 ppm
MISTRAL 613	690	470	405
MISTRAL 817	2100	1370	1270
MISTRAL 919	3100	2180	1860
MISTRAL 822	3100	2180	1860
MISTRAL 1023	5250	3400	2950

Installation data

Width	275 mm
Depth	440 mm
Inlet	3/4" BSP female or male
Outlet	3/4" BSP female or male
Drain	1/2" BSP female or male
Overflow	1/2" hose spigot
Power	2 volt, 50 Hz, 3 amp fuse (transformer supplied)

Maximum operating pressure	120 psi
Minimum operating pressure	20 psi
Maximum water temperature	50° C
Minimum operating temperature	Protect from frost

Call your local dealer



for a quotation now